

GATE VALVES

Welded End Forged Steel Gate Valves



Forged Steel Socket Weld Gate Valves 800 PSI A105


Features

- Connection End: Socket Weld
- Size: 1/2" – 2" (DN15 – DN50)
- Valve Body Material: A105
- Working Pressure: 800 PSI
- Applicable Medium: General oil, gas and water applications
- Temperature Range: -29°C to 425°C



Material List

No.	Part Name	Material
1	Body	ASTM A105
2	Seat	ASTM A276 410 + STL
3	Wedge	ASTM A276 420
4	Stem	ASTM A182 F6A
5	Gasket	SS304 + Graphite
6	Bonnet	ASTM A105
7	Bonnet Nut	ASTM A194 2H
8	Bonnet Bolt	ASTM A193 B7
9	Packing	Graphite
10	Pin	ASTM A307-A
11	Gland	ASTM A246 410
12	Gland Flange	ASTM A105
13	Gland Bolt	ASTM A193 B7
14	Gland Nut	ASTM A194 2H
15	Yoke Sleeve	ASTM A276 410
16	Lock Nut	Carbon Steel
17	Handwheel	ASTM A197



Technical Specifications

1. Basic design and manufacture according to API602/BS5352
2. Inspection and test for according to API 598
3. Socket welded dimension standard according to ASME B16.11

Main Technical Parameter			
Nominal Pressure		800 PSI	
Test Pressure	Shell Test	21.0	MPa
	Seal Test	15.4	
	Gas Test	0.6	
Max Working Temperature		-29°C to 425°C	
Applicable Medium: General oil, gas & water			

Ordering Information

VL - FS - GA - SW - 800 - 08
 I II III IV V VI

I Type of Item

VL Low Pressure Valves

II Material Grade

S	SS316, CF8M	CI	Cast Iron
FS	Forged Steel	CS	Cast Steel
B	Brass		

III Item

GA	Gate Valve	B1	1 PC Ball Valve
GL	Globe Valve	B2	2 PC Ball Valve
YS	Y-Strainer	B3	3 PC Ball Valve
SC	Swing Check Valve	BL	3 Way Ball Valve L Port
VC	Vertical Check Valve	BT	3 Way Ball Valve T Port
WC	Wafer Check Valve	BMF	Male x Female Mini Ball Valve
DD	Dual Disk	BU	Butterfly Valve

IV Connection Type

SW	S/W	G	BSPP
BW	B/W	N	NPT
R	BSPT	F	Flange End
W	Wafer	L	Lug

V Pressure

200	200 PSI	2000	2000 PSI
300	300 PSI	150	ANSI 150# Flange Standard
600	600 PSI	10K	JIS 10K Flange Standard
800	800 PSI	PN16	PN 16 Flange Standard
1000	1000 PSI		

For Inch OD & Inch NB Sizes
VI Size

Size	1/8"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
Code	02	04	05	06	08	10	12	16
Size	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"
Code	20	24	32	40	48	64	80	96

VII Coating

(None) No Additional Coating
 NI Nickel Plating

Dimension List

NPS	Ød	ØA	H	W	L	B	Weight (Kg)
1/2"	10.3	21.8	145	100	79	9.6	1.89
3/4"	13.5	27.1	145	100	92	12.7	2.42
1"	18	33.8	170	125	111	12.7	4.00
1 1/4"	23	42.6	190	160	120	12.7	5.54
1 1/2"	29	48.7	215	160	120	12.7	6.78
2"	36	61.2	240	180	140	12.7	10.35

Part Number Reference

Part No	Description
VL-FS-GA-SW-800-08	1/2" S/W GATE VALVE 800 PSI A105 OS&Y RISING STEM, STELLITE SEAT
VL-FS-GA-SW-800-12	3/4" S/W GATE VALVE 800 PSI A105 OS&Y RISING STEM, STELLITE SEAT
VL-FS-GA-SW-800-16	1" S/W GATE VALVE 800 PSI A105 OS&Y RISING STEM, STELLITE SEAT
VL-FS-GA-SW-800-20	1 1/4" S/W GATE VALVE 800 PSI A105 OS&Y RISING STEM, STELLITE SEAT
VL-FS-GA-SW-800-24	1 1/2" S/W GATE VALVE 800 PSI A105 OS&Y RISING STEM, STELLITE SEAT
VL-FS-GA-SW-800-32	2" S/W GATE VALVE 800 PSI A105 OS&Y RISING STEM, STELLITE SEAT

Chuan Kok Hardware & Machinery Pte Ltd

Address : 1783 Geylang Bahru, #01-02, Singapore 339708
Telephone Number : +65 6294 2566
Email Address : info@chuankok.com
Website : www.chuankok.com
Business Registration Number : 198201577Z
Country of Registration : Singapore

Conditions of Use of Catalogue:

The information in the catalogue are not binding and in order to improve distribution, Chuan Kok Hardware & Machinery Pte Ltd reserves the right to make any change including size and pressure ratings considered necessary at any time and without prior notice. According to the copyright and the civil law, any reproduction (also partial) of figures and texts of this catalogue by means of electronic, mechanical, photocopies, microfilms, recordings or other is forbidden without Chuan Kok Hardware & Machinery Pte Ltd's authorization.
Catalogue Version: 2021

