



Figure 1 SAE Flanges

Introduction:

SAE flange is a hydraulic flange that made in accordance to SAE J518 / ISO 6162 standards. SAE flanges are normally supplied for oil hydraulic systems in extensive range such as shipbuilding, oil and gas, mobile hydraulic systems and where there is a passage of oil.

Material:

SAE flanges are fabricated by two kinds of materials which is steel (ST52.3) and stainless steel (AISI SS316L). SAE flange are made from normalized forgings from raw material.

Size Range & Pressure Rating:

SAE flange are available in nominal sizes ranged from 3/8" (DN10) to 5" (DN125). The pressure rating of SAE flange can be defined to two series: Code 61 Series and Code 62 Series.

The working pressure for Code 61 series are ranged from 34 Bar to 345 Bar, depends on the sizes. While for Code 62 series, the working pressure are 414 Bar. However, the pressure rating of SAE flanges and connected equipment combination might vary from each other.



Figure 2 Flat Side SAE Flange

Connections Type & Configurations:

For the connections of SAE flanges, it usually available in few types: threaded (NPT / BSPP), welding (Socket Weld / Butt Weld), blind flanges, and split flanges.



Figure 3 Oring Side SAE Flange

SAE flanges are available in two types: Flat Side and Oring Side. Flat side of SAE flange are SAE flange that come with bolt thread (UNC / Metric) and oring side of SAE flange are SAE flange that contains a groove seat to place a rubber o-ring. Flanges with oring are has an advantage of prevent leakage as all metal-to-metal flanges are more prone to leakage.

The configurations of SAE flanges are flat side, oring side or complete set. A complete set of SAE flanges are combination of flat side and oring side where it forms a seal between the flat surface and oring side held in a recessed circular groove in the other half. By tightening the bolts, it draws flat side and oring side together and compresses the oring.

SAE flange complete set is tightened by using socket head cap screws and spring washers according to the recommended torque value. According to SAE J518 standard, the lengths of cap screws are usually shorter than the overall length of SAE flange complete set.

Chuan Kok Hardware & Machinery Pte Ltd

Address: 1783 Geylang Bahru #01-02, Kallang Distripark Singapore 339708

Telephone Number: +65 6294 2566

Fax Number: +65 6295 7013

Email Address: info@chuankok.com

Website: www.chuankok.com

Business Registration Number: 198201577Z

Country of Registration: Singapore

Conditions of Use of Catalogue

The information in the catalogue are not binding and in order to improve distribution, Chuan Kok Hardware & Machinery Pte Ltd reserves the right to make any change including size and pressure ratings considered necessary at any time and without prior notice.

According to the copyright and the civil law, any reproduction (also partial) of figures and texts of this catalogue by means of electronic, mechanical, photocopies, microfilms, recordings or other is forbidden without Chuan Kok Hardware & Machinery Pte Ltd's authorization.

Catalogue Version: 0616