



RFS HYDRAULICS
CREATING OPPORTUNITIES



GS HYDRO BONDED SEALS

Specifications

ISO 6162 / ISO 6164

Material Specifications

Metallic Ring: Steel/ Stainless Steel

Size Range

1/2" – 8"

Size Available

ANSI 36.10

ANSI 36.19

Metric size




GS Bonded Seals

Features

- Used in pipeline systems and provide a tight end to end connection to prevent leakage
- The seal consists of a metallic ring and a nitrile rubber seal (NBR) which joined together
- Nitrile rubber (NBR rubber)
 - An elastomer material
 - Can withstand temperature ranging from -35°C to +120°C
 - Great resistance to petroleum products, wear and tear, flame retarded fluids, abrasion and compression
- Stainless steel metallic ring (SS302)
 - Excellent resistance against corrosion
 - Resistant to harsh weather conditions
 - Also contain other elements that makes it resistant to corrosion such as:


Elements	Content (%)
Chromium (Cr)	18.2
Manganese (Mn)	1.6
Carbon (C)	0.06
Iron (Fe)	Balance
Nickel (Ni)	8.5
Silicon (Si)	0.5

Bonded Seal
ISO 6162 (SAE J 518)

Bonded Seal for Metric GS-pipe Ends

Size	STD Part No	SS Part No	S	D	D1
1/2"	0823	0823SS	2.03	23.80	17.28
3/4"	1213	1213SS	2.34	33.27	24.26
1"	1629	1629SS	2.34	34.93	27.05
1 1/4"	2030	2030SS	3.25	42.80	33.89
1 1/2"	2432	2432SS	3.25	52.38	42.93
2"	3219	3219SS	3.25	63.50	51.69
2 1/2"	4037	4037SS	3.25	75.00	64.39
3"	4839	4839SS	3.25	90.17	76.08

Bonded Seal for ANSI 36.10/36.19 GS-pipe Ends

Size	STD Part No	SS Part No	S	D	D1
1/2"	0821	0821SS	2.00	15.88	10.37
3/4"	0823	0823SS	2.03	23.80	17.28
1"	1633	1633SS	2.34	28.58	21.54
1 1/4"	2042	2042SS	2.34	39.00	31.00
1 1/2"	2448	2448SS	3.25	44.45	35.94
2"	3260	3260SS	3.25	55.50	46.50
2 1/2"	4073	4073SS	3.25	69.85	54.89
3"	4888	4888SS	4.00	83.80	70.00

Bonded Seal
ISO 6164

Bonded Seal for Metric GS-pipe Ends

Size	STD Part No	SS Part No	S	D	D1
2"	3219	3219SS	3.25	63.50	51.69
2 1/2"	4037	4037SS	3.25	75.00	64.39
3"	4839	4839SS	3.25	90.17	76.08
4"	5644	5644SS	4.00	110.0	95.00
4 1/2"	6000	6000SS	4.00	126.0	108.0
5"	6455	6455SS	5.00	143.7	127.0
6"	8001	8001SS	8.00	181.0	155.0
8"	9600	9600SS	9.00	240.0	205.0

Bonded Seal for ANSI 36.10/36.19 GS-pipe Ends

Size	STD Part No	SS Part No	S	D	D1
2"	3260	3260SS	3.25	55.50	46.50
2 1/2"	4073	4073SS	3.25	69.85	54.89
3"	4888	4888SS	4.00	83.80	70.00
4"	5644	5644SS	4.00	110.0	95.00

RFS Hydraulics

Conditions of Use of Catalogue:

The information in the catalogue are not binding and in order to improve distribution, RFS Hydraulics Sdn Bhd reserves the right to make any change including size and pressure ratings considered necessary at any time and without prior notice. According to the copyright and the civil law, any reproduction (also partial) of figures and texts of this catalogue by means of electronic, mechanical, photocopies, microfilms, recordings or other is forbidden without RFS Hydraulics Sdn Bhd's authorization.
Catalogue Version: 2020